



ARLON

FUSION WRAP + FLITE™ TECHNOLOGY

Specifying the right product could be the difference between bidding on or winning a job. Fusion Wrap featuring FLITE Technology™ can be the product of choice in various situations: when cost-driven opportunities are presented, if shorter to medium term durability is specified, or when a flat to simple curve vehicle wrap application is present. A polymeric film specifically designed for vehicle wraps, the thin and flexible film facilitates ease of use and efficiency. The lite initial contact adhesive system from FLITE Technology™ will ensure repositionability, developing a quick anchor tack to speed up installations. Pair with Series 3170 intermediate cast overlamine for the thinnest hybrid installation.

Unique Features:

- ▶ Product of Choice in Cost-Driven Opportunities
- ▶ Thin, Flexible, High-Performance Polymeric Film Facilitating Easier Handling and Installation
- ▶ Clean Removability up to 2 Years on Most Vehicle Wrap Application
- ▶ Added Repositionability During Installation Building a Quick Bond
- ▶ Superior Conformability and Stretch for a Polymeric Wrap Film

Applications:

- ▶ Vehicle Wraps

Performance & Physical Data

Finish:	Gloss
Durability (Unprinted):	7 Years
Roll Widths:	1.37m / 1.52m
Roll Lengths:	45.72 m
Adhesive:	Clean Removing, Repositionable (Light Grey)
Release Liner:	Lay-Flat Polycoated with Low Profile FLITE Technology™
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlamine:	Series 3170 Series 3210 Series 3220 Series 3270 Series 3420*

**Use on flat and simple curves only
To ensure a successful vehicle wrap application, please read through Arlon's Fusion Wrap Installation Guide.*



Certified for HP Latex Inks

USA: a 200 Boysenberry Lane, Placentia, CA 92870, USA
EUROPE: a North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

p 800 232 7161 / 714 985 6300 f 800 329 2756
p +31 0 70 354 4311 f +31 0 70 355 7721

arlon.com

March 2019